

Revision nr 1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 1/11

Safety data sheet according to U.S.A. Federal Hazcom 2012

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DOMO 10 CARTUCCIA Product name

COLLA EPOSSIDICA PARTE A CONTENENTE RESINA EPOSSIDICA LIQUIDA Chemical name and synonym

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **EPOXY GLUE FOR STONES (PART A).**

1.3. Details of the supplier of the safety data sheet

Name Tenax Spa Full address Via I Maggio, 226 District and Country 37020

(VR) Volargne

Italy

+39 045 6887593 Tel. Fax +39 045 6862456

e-mail address of the competent person

responsible for the Safety Data Sheet msds@tenax.it

TENAX USA - 7606 Whitehall Executive Center Drive - Unit 400 - Charlotte NC Product distribution by

28273 Tel. +1 704-583-1173 - Tel: (800) 341 0432 - Fax +1 704-583-3166 -

info@tenaxusa.com

1.4. Emergency telephone number

For urgent inquiries refer to 1-800-5355053 (1-352-323-3500 international)

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement.

Germ cell mutagenicity, category 2 Skin corrosion, category 1B Serious eye damage, category 1 Skin sensitization, category 1

Suspected of causing genetic defects. Causes severe skin burns and eye damage. Causes serious eye damage. May cause an allergic skin reaction.

Hazard pictograms:







Signal words:

Danger

Hazard statements: H341

Suspected of causing genetic defects H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

Precautionary statements:

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

P202 P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P264 Wash . . . thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. P272

P280 Wear protective gloves / clothing and eye / face protection.

Response:



Revision nr 1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 2/11

SECTION 2. Hazards identification

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P302+P352 IF ON SKIN: wash with plenty of water /

IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower. P303+P361+P353

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER / doctor / . . Wash contaminated clothing before reuse. P363

Storage:

Store locked up

Disposal: P501

Dispose of contents / container according to applicable law

2.2. Other hazards.

Environmental classification as for Reg. (EU) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement.

Hazardous to the aquatic environment, chronic toxicity, category 3 Harmful to aquatic life with long lasting effects

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

Prevention:

Avoid release to the environment.

Response:

Storage:

Disposal:

Dispose of contents / container according to applicable law.

Additional hazards. Corrosive to the respiratory tract.

Contains epoxy constituents. May produce an allergic reaction.

Additional hazards

Corrosive to the respiratory tract.

Contains epoxy constituents. May produce an allergic reaction.

SECTION 3. Composition/information on ingredients

3.1. Substances.

Information not relevant.

3.2 Mixtures

Contains:

Identification. Classification: Conc. %.

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)

CAS. 25068-38-6 20 - 30 Eye irritation, category 2 H319, Skin irritation, category 2 H315, Skin sensitization, category 1 H317,

Hazardous to the aquatic environment, chronic toxicity, category 2 H411

1,6-HEXANEDIOL DIGLYCIDYL ETHER Eye irritation, category 2 H319, Skin irritation, category 2 H315, Skin sensitization, category 1 H317, CAS. 16096-31-4 10 - 20

Hazardous to the aquatic environment, chronic toxicity, category 3 H412

Formaldehyde, polymer with MXDA and phenol

CAS 57214-10-5 5 - 10 Skin corrosion, category 1B H314, Skin sensitization, category 1 H317

BENZYL ALCOHOL 100-51-6 CAS

3.5 - 6Acute toxicity, category 4 H302, Acute toxicity, category 4 H332

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

CAS 2855-13-2 2.5 - 5 Acute toxicity, category 4 H302, Acute toxicity, category 4 H312, Skin corrosion, category 1B H314, Skin sensitization,

category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 3 H412

2,3-EPOXYPROPYL NEODECANOATE

Germ cell mutagenicity, category 2 H341, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 2 H411

METAXYLENDIAMINE

1 - 3 Acute toxicity, category 4 H302, Acute toxicity, category 4 H332, Skin corrosion, category 1B H314, Skin sensitization, 1477-55-0 CAS.

category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 3 H412

PHENOL

CAS. 108-95-2 0.3 - 0.35Germ cell mutagenicity, category 2 H341, Acute toxicity, category 3 H301, Acute toxicity, category 3 H311, Acute toxicity, category 3 H331, Specific target organ toxicity - repeated exposure, category 2 H373, Skin corrosion, category 1B H314

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.



Revision nr.1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 3 / 11

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.



Revision nr.1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 4 / 11

SECTION 7. Handling and storage. .../>>

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

USA NIOSH-REL NIOSH publication No. 2005-149, 3th printing, 2007.

USA OSHA-PEL Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.

USA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits

(PELs).

				METAXYL	ENDIAMINE .	
Threshold Limit Value.						
Type	Country	TWA/8h		STEL/15r		
		mg/m3	ppm	mg/m3	ppm	
CAL/OSHA	USA	0.1				SKIN.
NIOSH	USA			0.1 (C)		SKIN.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

(302 °F)

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance Colour . white Odour typical Odour threshold. Not available Not available. pH. Melting point / freezing point. Not available. Initial boiling point. Not available Boiling range. Not available. Flash point. 150

Evaporation rate Not available. Flammability (solid, gas) Not available.

©EPY 9.1.4 - SDS 1003



Revision nr.1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 5 / 11

SECTION 9. Physical and chemical properties./

Lower inflammability limit. Not available Upper inflammability limit. Not available Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Vapour density Not available. Relative density. 1.35 Kg/l insoluble in water Solubility Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Decomposition temperature. Not available. Viscosity Not available. Explosive properties Not available Oxidising properties Not available.

9.2. Other information.

Solid content. 100,00 %

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

BENZYL ALCOHOL: decomposes at temperatures higher than 870°C/1598°F with possibility of explosion.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL: may react dangerously with: hydrobromic acid and iron in the presence of heat, oxidising agents and sulphuric acid. Risk of explosion on contact with: phosphorus trichloride.

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE: can react dangerously with strong oxidising agents and concentrated acids.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

BENZYL ALCOHOL: avoid exposure to the air, sources of heat and naked flames.

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE: avoid contact with strong oxidising agents and acids.

10.5. Incompatible materials.

BENZYL ALCOHOL: sulphuric acid, oxidising substances and aluminium.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible mutagenic effects. Anyway, currently available data are insufficient to definitively prove hereditary gene alterations.

This product is corrosive and causes serious burns and vesicles on the skin, which can arise even after exposure. Burns are very stinging and painful. Upon contact with eyes, it may cause serious harm, such as cornea opacity, iris lesions, irreversible eye coloration.

The vapors and/or powders are caustic for the respiratory system and may cause pulmonary edema, whose symptoms sometimes arise only after some hours. Exposure symptoms may include: sting, cough, asthma, laryngitis, respiratory disorders, headache, nausea and sickness. If swallowed, it may cause mouth, throat and oesophagus burns, sickness, diarrhoea, edema, larynx swelling and, consequently, asphyxia. Perforation of the gastro-intestinal tract is also possible.

This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas.

Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

Highly corrosive: causes severe damage to the respiratory tract in the event of inhalation.



Revision nr.1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 6 / 11

SECTION 11. Toxicological information. .../>

This product contains epoxy resins. Producer's specifications are as follows: Because of epoxy-product properties and according to the toxicological data available for similar products, this preparation may sensitize and irritate the skin and the respiratory system. It contains epoxy components at low molecular weights, which may irritate eyes, mucosas and skin. Frequent contact with skin may cause irritation and sensitization phenomena. Sensitization reactions may also be caused by other epoxy components (cross-sensitization). Avoid contact with skin and exposure to vapours and aerosols.

BENZYL ALCOHOL

LD50 (Oral). 1230 mg/kg Rat LD50 (Dermal). 2000 mg/kg Rabbit LC50 (Inhalation). > 4.1 mg/l/4h Rat

PHENOL

LD50 (Oral). 282 mg/kg Rat LD50 (Dermal). 660 mg/kg Rat

2.3-EPOXYPROPYL NEODECANOATE

 LD50 (Oral).
 9600 mg/Kg Ratto

 LD50 (Dermal).
 3800 mg/Kg Ratto

 LC50 (Inhalation).
 > 240 mg/m3 Ratto (4 ore)

METAXYLENDIAMINE

 LD50 (Oral).
 930 mg/kg rat

 LD50 (Dermal).
 > 3100 mg/kg rabbit

 LC50 (Inhalation).
 1.34 mg/L rat (fog)

Carcinogenicity Assessment: 108-95-2 PHENOL

ACGIH:: A4 IARC:3

SECTION 12. Ecological information.

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity.

2,3-EPOXYPROPYL NEODECANOATE

LC50 - for Fish. 9.6 mg/l/96h

EC50 - for Crustacea. 3.5 mg/l/48h Dafnia (2 gg)

METAXYLENDIAMINE

LC50 - for Fish. 87.6 mg/l/96h oryzias latipes EC50 - for Crustacea. 87.6 mg/l/48h daphnia magna

EC50 - for Algae / Aquatic Plants. 20.3 mg/l/72h selenastrum capricornutum

mg/l 0.1 - 100

Chronic NOEC for Crustacea. 4.7 mg/l 21d Chronic NOEC for Algae / Aquatic Plants. 4.7 mg/l 72 h

12.2. Persistence and degradability.

BENZYL ALCOHOL Rapidly biodegradable.

Solubility in water.

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)

NOT rapidly biodegradable.

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Solubility in water. mg/l 1000 - 10000

NOT rapidly biodegradable.

PHENOL

Rapidly biodegradable.



Revision nr.1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 7 / 11

SECTION 12. Ecological information. .../>>

METAXYLENDIAMINE Entirely biodegradable.

12.3. Bioaccumulative potential.

BENZYL ALCOHOL

Partition coefficient: n-octanol/water. 1.1

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)
Partition coefficient: n-octanol/water. > 2.918
BCF. 31

PHENOL

Partition coefficient: n-octanol/water. 1.47

12.4. Mobility in soil.

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN)
Partition coefficient: soil/water. 2.65

12.5. Results of PBT and vPvB assessment.

Information not available.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to dangerous goods transport regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, IATA: 3316

14.2. UN proper shipping name.

ADR / RID: CHEMICAL KIT IMDG: CHEMICAL KIT IATA: CHEMICAL KIT CHEMICAL KIT

14.3. Transport hazard class(es).

ADR / RID: Class: 9 Label: 9

IMDG: Class: 9 Label: 9

IATA: Class: 9 Label: 9



14.4. Packing group.

ADR / RID, IMDG, IATA:



Revision nr.1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 8 / 11

Packaging instructions: 964

Packaging instructions: 964

SECTION 14. Transport information. .../>>

14.5. Environmental hazards.

ADR / RID: Environmentally Hazardous.

IMDG: Marine Pollutant.

IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user.

ADR / RID: HIN - Kemler: 90 Limited Quantities 5 It Tunnel restriction code (E)

Special Provision:
IMDG: EMS: F-A, S-F Limited Quantities 5 It

IATA: Maximum quantity: 45

Cargo: Maximum quantity: 450 L
Pass.: Maximum quantity: 450 L

Special Instructions: A97, A158

•

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

U.S. Federal Regulations.

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

108-95-2 PHENOL (Phenols)

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

108-95-2 PHENOL (Phenols)

Clean Water Act – Toxic Pollutants:

108-95-2 PHENOL (Phenols)

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

108-95-2 PHENOL (Phenols)

EPCRA 302 EHS TPQ:

108-95-2 PHENOL (Phenols)

EPCRA 304 EHS RQ:

108-95-2 PHENOL (Phenols)

CERCLA RQ:

108-95-2 PHENOL (Phenols)



Revision nr.1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 9 / 11

SECTION 15. Regulatory information. .../>>

EPCRA 313 TRI:

108-95-2 PHENOL (Phenols)

RCRA Code:

108-95-2 PHENOL (Phenols)

CAA 112 (r) RMP TQ: No component(s) listed.

State Regulations.

Massachussetts:

100-51-6 BENZYL ALCOHOL 108-95-2 PHENOL (Phenols)

1477-55-0

Minnesota:

100-51-6 BENZYL ALCOHOL 108-95-2 PHENOL (Phenols)

1477-55-0

New Jersey:

2855-13-2 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

108-95-2 PHENOL (Phenols)

1477-55-0

New York:

108-95-2 PHENOL (Phenols)

Pennsylvania:

100-51-6 BENZYL ALCOHOL 108-95-2 PHENOL (Phenols)

1477-55-0

California: 90-72-2

2,4,6-TRIS(DIMETHYLAMINOMETHYL) PHENOL (Phenols)

25068-38-6 REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN) (Phenols)

108-95-2 PHENOL (Phenols)

1477-55-0

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Candadian WHMIS.

Information not available.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Muta. 2 Germ cell mutagenicity, category 2
Acute Tox. 3 Acute toxicity, category 3
Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Skin Corr. 1B
Skin corrosion, category 1B
Skin Corr. 1C
Skin corrosion, category 1C
Eye Dam. 1
Eye Irrit. 2
Skin irrit. 2
Skin irrit. 2
Skin irrit. 2
Skin irritation, category 2
Skin Sens. 1
Skin sensitization, category 1

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3
Aquatic Chronic 4 Hazardous to the aquatic environment, chronic toxicity, category 4



Revision nr.1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 10 / 11

SECTION 16. Other information. .../>>

H341 Suspected of causing genetic defects.
H301 Toxic if swallowed.

 H301
 Toxic if swallowed.

 H311
 Toxic in contact with skin.

 H331
 Toxic if inhaled.

 H302
 Harmful if swallowed.

 H312
 Harmful in contact with skin.

H332 Harmful if inhaled.

May cause damage to organs through prolonged or repeated exposure.

H314 Causes severe skin burns and eye damage
H318 Causes serious eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

LEGEND:

H373

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website



Revision nr.1 Dated 8/25/2015 Printed on 10/2/2015 Page n. 11 / 11

SECTION 16. Other information. .../>>

- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.